

Microwave antenna

AL1-28/MER

ALCOMA

Microwave antenna description

High Performance 0.35 m antenna for point to point links.

General parameters

Diameter	0.35 m (1 ft.)
Feeder	single polarized
Input flange standard	circular, hole diameter 8.0 mm
- optional	IEC UBR 220
Polarization	horizontal or vertical
Environmental temperature	-45 °C až +55 °C
Color	light gray
Radom color	white
Radom material	plastic (ABS)

Electrical parameters


Frequency band	27.5 - 29.5 GHz
Gain mid band	36.9 dBi
3dB - BW	2.2° (H/ V)
Return loss	> 1.20 (20 dB)
F/B ratio	63 dB
XPD	30 dB
Class	2 or 3 (ETSI EN 302 217-4-2)



Microwave antenna AL1-28/MER

Mechanical parameters

Performance stability	up to 30 m/s (110 km/h)
Survival	up to 55 m/s (200 km/h)
Net weight	5.6 kg
Pipe diameter	38 - 115 mm
Adjust Azimuth	$\pm 180^\circ$
Adjust Elevation	$\pm 25^\circ$



Forces and twisting moment due wind and ice

Wind velocity	30 m/s (110 km/h)	55 m/s (200 km/h)
F_a - axial force	90 N	270 N
F_s - side force	30 N	85 N
M_r - twisting moment	25 Nm	65 Nm
Vertical load due to radial ice 25 mm (ice density 7kN/m ³)		70 N

Outlines

