

Microwave antenna

AL3-11/MPR

ALCOMA

Microwave antenna description



High Performance 0.90 m antenna for point to point links.

General parameters

Diameter	0.9 m (3 ft.)
Feeder	single polarized
Input flange standard	circular, hole diameter 19.05 mm
- optional	IEC R100 (WR90)
Polarization	horizontal / vertical
Environmental temperature	-45 °C ÷ +55 °C
Color	gray
Radom material	plastic tilt
Radom color	white

Electrical parameters


Frequency band	10.700 - 11.700 GHz
Gain mid band	37.1 dBi
3dB - BW	2.2° (H/ V)
Return loss	> 1.2 (20 dB)
F/B ratio	58 dB
XPD	30 dB
Class	2 or 3 (ETSI EN 302 217)



Microwave antenna AL3-11/MPR

Mechanical parameters

Performance stability	up to 30 m/s (110 km/h)
Survival	up to 55 m/s (200 km/h)
Net weight	26 kg
Pipe diameter	73 - 115 mm
Fine adjust Azimuth	$\pm 7^\circ$
Fine adjust Elevation	$\pm 15^\circ$



Forces and twisting moment due wind and ice

Wind velocity	30 m/s (110 km/h)	55 m/s (200 km/h)
F_a - axial force	560 N	1850 N
F_s - side force	180 N	570 N
M_T - twisting moment	200 Nm	640 Nm
Vertical load due to radial ice 25 mm (ice density 7kN/m ³)	430 N	

Outlines

